

FEATURES

- High output 5th order Band-Pass design
- Premium European High Efficiency custom IDEA dual 18" transducers
- Dual Neutrik NL4 connectors
- 4 Ohm Passive
- Rugged and durable 18 mm birch plywood construction and finish
- Durable paint coating process, available in standard textured black or white
- Optional RAL colors (on demand)
- Four integrated handles and two 36 mm pole cups (V/H)
- Compatible rigging accessories (optional) for stacked and flown configurations



APPLICATIONS

- High SPL A/V, portable professional sound reinforcement and touring
- Flown subwoofer in fixed installations for concert venues and sports arenas
- Main or distributed subwoofer system in Pubs, Lounges, Bars and clubs



OVERVIEW

BASSO Series models allow the user to choose the most adequate subwoofer for any given situation from within a family of products with common finish, design solutions and performance philosophy as well as shared rigging and transport accessories.

BASSO36t is compact Dual 18" multipurpose high output subwoofer for a very wide range of configurations of both professional portable sound reinforcement, touring and premium installations.

Like All IDEA Loudspeakers **BASSO36t** is built with the necessary structural strength and finish quality required for durable touring use. Its high quality 18 mm birch plywood enclosure covered with IDEA Aquaforce custom paint solution and a 2 mm steel front grill will keep your equipment safe and brand new after hours of heavy touring.

BASSO36t features four integrated handles and two 35 mm pole mount sockets for vertical and horizontal set-ups. Optional wheels kit is also available.

BASSO36t is compatible with optional **BASSO** rigging frames for ground-stacked configurations (see instructions for ground-stacked set-ups with **BASSO** rigging frames).

TECHNICAL DATA

Enclosure design	Band Pass
Transducers	2 x 18"
Power Handling (RMS)	2.4 kW
Nominal Impedance	4 Ohm
SPL (Continuous/Peak)	135/141 dB SPL
Frequency Range (-10 dB)	45 - 120/150/180/200 Hz
Frequency Range (-3 dB)	54 - 100/120/145/160 Hz
Dimensions (WxHxD)	900 x 600 x 850 mm (35.4 x 23.6 x 33.5 in)
Weight	89 kg (196.2 lb)
Connectors	2 x Neutrik speakOn NL-4 in parallel
+/-1	Input
+/-2	Link
Cabinet Construction	18 mm Plywood
Grille	2 mm perforated weatherised steel with protective foam
Finish	Durable IDEA proprietary Aquaforce paint coating process
Handles	4 integrated handles
Feet/Skates	2 skates
Installation	36 mm Pole mount sockets (H/V)
Accessories	Riggin Frame (RF-900) Riggin Frame adaptor (RF-9060) Riggin System (R5-BASSO-L) 35 mm Pole (K&M-21336)

TECHNICAL DRAWINGS

